

1. Product Information about Energy-Efficient Drives

In the following you will find the product information about energy-efficient drives according to the requirements of the **COMMISSION REGULATION (EC) No 640/2009**. These will apply for the production years 2018 - 2020.

Requirements acc. to EG 640 / 2009 Annex 1 Ch.2		Reference
1.	nominal efficiency at 100%, 75%, 50%	Siehe table chapter 2
2.	efficiency level	Name plate information – see chapter 4
3.	year of manufacture	Name plate information – see chapter 4
4.	place of Fa. ABM Greiffenberger Antriebstechnik GmbH	See chapter 6
5.	product's model number	Name plate information – see chapter 4
6.	number of poles	Name plate information – see chapter 4
7.	rated power output	Name plate information – see chapter 4
8.	rated input frequency	Name plate information – see chapter 4
9.	rated voltage	Name plate information – see chapter 4
10.	rated speed	Name plate information – see chapter 4
11.	information relevant at end-of-life	See chapter 5
12.	information on the range of operating conditions	See chapter 3

2. Tabellen Nenneffizienz Tables Nominal Efficiency

Three-phase asynchronous with efficiency level IE2 2018 - 2020

P _N kW	Typ	η % bei Last		
		100	75	50
2-polig 50 Hz 400 V				
0,75	D80e-2	78,9	78,0	74,2
1,1	D80Mf-2	81,7	82,8	79,4
1,5	D90Sb-2	81,6	82,1	80,3
2,2	D90Lb-2	84,5	85,5	84,7
3,0	D100Lb-2	85,4	85,5	83,4
4,0	D100Lc-2	85,8	86,5	85,7
5,5	D112Me-2	87,9	87,9	86,2
7,5	D132Mc-2	89,5	89,2	87,4
11,0	D132Me-2	90,1	90,1	88,8
4-polig 50 Hz 400 V				
0,75	D80Mf-4	81,0	82,0	80,8
	D90Sb-4	81,8	82,6	81,3
1,1	D90Lb-4	83,1	83,7	82,1
1,5	D90Ld-4	83,7	84,7	83,5
2,2	D100Lc-4	85,8	86,5	85,4
3,0	D100L-4	86,5	87,1	86,1
4,0	D112M-4	88,3	88,5	87,2
5,5	D132Mb-4	88,9	89,4	88,5
7,5	D132Mc-4	88,7	89,1	88,3
11,0	D132M-4	89,8	90,3	89,6
6-polig 50 Hz 400 V				
1,5	D100Lc-6	81,9	82,3	80,0

Three-phase asynchronous with efficiency level IE3 2018 - 2020

P _N kW	Typ	η % bei Last		
		100	75	50
2-polig 50 Hz 400 V				
0,75	D80e-2	82,9	82,9	80,9
1,1	D80Mf-2	84,4	84,9	83,4
1,5	D90Sb-2	84,9	84,8	82,5
2,2	D90Lb-2	85,9	86,1	84,5
3,0	D100Lb-2	88,0	87,7	85,7
4,0	D100Ld-2	88,1	88,3	86,9
	D112M-2	89,4	89,0	88,7
5,5	D112Me-2	90,5	90,5	89,2
7,5	D132Mc-2	90,5	90,0	88,0
11,0	D132Me-2	92,3	92,1	90,7
4-polig 50 Hz 400 V				
0,75	D80Lh-4	82,7	82,1	78,9
	D90Lb-4	83,5	83,4	80,9
1,1	D90Ld-4	85,3	85,3	83,4
1,5	D100Lc-4	86,8	86,9	85,1
2,2	D100L-4	87,0	87,1	85,4
3,0	D112Mc-4	88,3	87,9	85,8
4,0	D112M-4	89,1	88,8	87,0
5,5	D132Mc-4	90,7	90,9	89,9
7,5	D132Md-4	90,9	90,8	89,4
6-polig 50 Hz 400 V				
0,75	D90Lc-6	79,1	77,8	73,5
1,1	D100Lc-6	83,1	82,2	78,8



3. Operating Conditions

Our energy-efficient drives are designed for the ambient conditions according to EN 60034-1 respectively EN 60204-1:

Ambient conditions	Requirement
Ambient temperatures	-15° up to +40 °C
Installation height	≤ 1000 m above sea level
Humidity	Up to 50% (at +40°) Up to 90% (at room temperature)

4. Description of Name Plate

On the name plate you can find informations like efficiency level, year of manufacture and part number


		Greiffenberger Antriebstechnik / www.abm—drives.com			
Made in Germany		D Mot	Nr	TNr 020022062	
Typ 4DF100L-4	VDE0530	IKI F	UT	C	IP 54
S 1	ETA 87,0 IE 3				LW
2,2	kW	230/400	V	50	Hz
Δ Y	8,0/4,6	A	cos 0,80		
1440					1/min
BREMSE	TS	Nm	V	A	CB CA

Abbreviation	Unit	Designation	
Mot		D = three-phase motor	
Nr		Order number - serial number – balancing (F/H)	
TNr		ABM-part number (complies w. model number of VO 640/2009)	
IKL		Insulation class	
UT	°C	Maximum permissible ambient temperature (if contrary to standard)	
IP		Protection class	
Typ		ABM-Type	
LW		Delivery week and year (complies w. year of manufacture of VO 640/2009)	
		Operating mode – degree of efficiency – efficiency level	
	kW	Rated power output	
	V	Rated voltage	
	Hz	Rated input frequency	
		Connection (Delta / Star)	
	A	Rated current of motor	
		Cos-Phi of the motors	
	1/min	Rated speed at output shaft	
Bremse	TS	Nm	Braking torque (not for IE drives)
		V	Brake supply voltage (not for IE drives)
		A	Rated current of brake (not for IE drives)
CB	µF	Operating capacitor for single phase motor (not for IE drives)	
CA	µF	Starting capacitor for single phase motor (not for IE drives)	

5. Decommissioning and disposal

5.1. Decommissioning

- First, remove the electrical connections


 **Danger**

ELECTRIC SHOCK

Electrical parts are energized with hazardous voltage. When touching these parts you will get an electric shock. Death or severe injuries are the result.

- Any electrical work for the decommissioning must only be carried out by qualified specialists!
- Electrical work must only be carried out if the system is de-energised and secured against restart!

- For gear with oil filling: remove the lubricant
- Remove the drive from the machine
- Transport the drive to the work station prepared for the disassembly.
- Protect the drive and the components against falling when disassembling

 **Danger**

FALLING OBJECTS

Falling objects can cause severe injuries.

- Ensure secure fastening!

5.2. Recycling and disposal

Divide the components into the following category for recycling:

- Electronic scrap (e.g. circuit boards)
- Iron scrap (e.g. stator and rotor sheets)
- Aluminium (e.g. housing, rotor grouting)
- Copper (e.g. motor winding)
- Synthetics (e.g. insulation material, cables)

Dispose of the components in compliance with the national and local regulations or contact a waste disposal company. Dispose oil and grease of attached gears according to local regulations.

6. Addresses



Germany

ABM Greiffenberger Antriebstechnik GmbH
Postfach 140 Friedenfelser Str. 24
D - 95614 Marktrechwitz

Tel.: +49 9231 67-0
Fax: +49 9231 67-5295
E-Mail: vk@abm-antriebe.de



USA

ABM DRIVES INC.
394 Wards Corner Road · Suite 110
Loveland, OH 45140

Tel.: +1 513 5761300
Fax: +1 513 5764999
E-Mail: abmus@abm-drives.com



Austria

ABM Antriebstechnik GmbH
Ortstraße 18/1/5-7
A - 2331 Vösendorf

Tel.: +43 1 69911620
Fax: +43 1 699116223
E-Mail: abm-austria@abm-antriebe.de



France

ABM Systèmes d'Entraînement S.A.R.L.
40, rue Jean Monet
Melpark Bat. 5
F - 68200 Mulhouse

Tel.: +33 3 89334401
Fax: +33 3 89334405
E-Mail: infofr@abm-drives.com



P.R. China

ABM Drives (Suzhou) Co., Ltd.
Kuachun Industrial Area Unit 9G,
Chun Hui Lu, Weiting Town
VR China - 215122 Suzhou

Tel.: +86 512 - 8717 1081
Fax: +86 512 - 8717 1084
E-Mail: info-cn@abm-drives.com



Turkey

ABM Greiffenberger Hareket Sistemleri Ticaret
Limited Şirketi
Barbaros Mah. Bezirgan Sok. No:3

Deluxia Suites A Blok Daire:17
Batı Ataşehir-İstanbul, TR 34746

Tel.: +90 216 2903525
Fax: +90 216 2903526
E-Mail: abmtr@abm-drives.com



India

ABM Drives India Private Limited
Lunkad Sky Vista, 308 Viman Nagar,
Near Dorabji Mall, Opp New Airport Road,
Pune - 411014