



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data


Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	134	
PFH _D	1.52E-09	
Mission time	20 years	
System response time	< 40 ms	
Dimensions (HxLxW)	111.5x45x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	12	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Safety relay circuits	3NO	400 part 14

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment



Internal wiring diagram



Code structure

CS MP204M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19


General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	373	
PFH _D	2.19E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x45x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	4	399 part 6
Decoupled digital inputs (Jx)	4	399 part 7
Inputs for frequency signals from 0 to 4 kHz (Fx)	4	400 part 9
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Pin assignment



Internal wiring diagram



Code structure

CS MP205M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data


Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	3314	
PFH _D	1.09E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x45x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	8	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	12	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment



Internal wiring diagram



Code structure

CS MP206M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19


General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	431	
PFH _D	7.08E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x45x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	4	399 part 6
Inputs for 4-20 mA analogue signals (Cx)	2	399 part 8
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Pin assignment



Internal wiring diagram



Code structure

CS MP207M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data


Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	633	
PFH _D	7.02E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x45x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	16	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor safety output circuits (OSx)	8 PNP	400 part 13

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment



Internal wiring diagram



Code structure

CS MP208M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data


Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	128	
PFH _D	1.88E-09	
Mission time	20 years	
System response time	< 40 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	24	399 part 6
Test outputs (Tx)	8	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Safety relay circuits	3NO	400 part 14

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment



Internal wiring diagram



Code structure

CS MP301M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	535	
PFH _D	1.57E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	24	399 part 6
Test outputs (Tx)	12	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment

T01 T02 T03 T04	T11 I11 T12 I12	I31 I32 I33 I34
A1 A2 24V 0V	T13 I13 T14 I14	I35 I36 I37 I38
PWR P1 P2	I11 I12	I31 I32 I33 I34
O01 O02 O03 O04	I13 I14	I35 I36 I37 I38
OS1 OS2 OS3 OS4	I21 I22	I41 I42 I43 I44
USB I23	I24	I45 I46 I47 I48
O01 O02 O03 O04	T21 I21 T22 I22	I41 I42 I43 I44
OS1 OS2 OS3 OS4	T23 I23 T24 I24	I45 I46 I47 I48

Internal wiring diagram



Code structure

CS MP302M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	485	
PFH _D	1.76E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	32	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment

T01 T02 T03 T04	I11 I12 I13 I14	I31 I32 I33 I34
A1 A2 24V 0V	I15 I16 I17 I18	I35 I36 I37 I38
PWR P1 P2	I11 I12 I13 I14	I31 I32 I33 I34
O01 O02 O03 O04	I15 I16 I17 I18	I35 I36 I37 I38
OS1 OS2 OS3 OS4	I21 I22 I23 I24	I41 I42 I43 I44
USB	I25 I26 I27 I28	I45 I46 I47 I48
O01 O02 O03 O04	I21 I22 I23 I24	I41 I42 I43 I44
OS1 OS2 OS3 OS4	I25 I26 I27 I28	I45 I46 I47 I48

Internal wiring diagram



Code structure

CS MP303M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	98	
PFH _D	2.05E-09	
Mission time	20 years	
System response time	< 40 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	28	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Safety relay circuits	3NO+1NO	400 part 14

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment

13 23 33 43 T11 T12 T13 T14	I31 I32 I33 I34
A1 A2 24V 0V I15 I16 I17 I18	I35 I36 I37 I38
pizzato CS MP304	
PWR P1 P2	I31 I32 I33 I34
O01 O02 O03 O04 I15 I16 I17 I18	I35 I36 I37 I38
K1 K2 K3 K4 I21 I22 I23 I24	I41 I42 I43 I44
USB I25 I26 I27 I28	I45 I46 I47 I48
O01 O02 O03 O04 I21 I22 I23 I24	I41 I42 I43 I44
I14 24 34 44 I25 I26 I27 I28	I45 I46 I47 I48

Internal wiring diagram



Code structure

CS MP304M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	535	
PFH _D	1.57E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	24	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	12	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment

T01 T02 T03 T04	I11 I12 I13 I14	I31 I32 I33 I34
A1 A2 24V 0V	I15 I16 I17 I18	I35 I36 I37 I38
pizzato CS MP305		
PWR P1 P2	I11 I12 I13 I14	I31 I32 I33 I34
O01 O02 O03 O04	I15 I16 I17 I18	I35 I36 I37 I38
OS1 OS2 OS3 OS4	I21 I22 I23 I24	O41 O42 O43 O44
USB	I25 I26 I27 I28	O45 O46 O47 O48
O01 O02 O03 O04	I21 I22 I23 I24	O41 O42 O43 O44
OS1 OS2 OS3 OS4	I25 I26 I27 I28	O45 O46 O47 O48

Internal wiring diagram



Code structure

CS MP305M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	100	
PFH _D	1.86E-09	
Mission time	20 years	
System response time	< 40 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	20	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	12	400 part 11
Safety relay circuits	3NO+1NO	400 part 14

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment

13 23 33 43 T11 T12 T13 T14	I31 I32 I33 I34
A1 A2 24V 0V I15 I16 I17 I18	I35 I36 I37 I38
pizzato CS MP306	
PWR P1 P2	I31 I32 I33 I34
O01 O02 O03 O04 I15 I16 I17 I18	I35 I36 I37 I38
K1 K2 K3 K4 I21 I22 I23 I24	O41 O42 O43 O44
USB I25 I26 I27 I28	O45 O46 O47 O48
O01 O02 O03 O04 I21 I22 I23 I24	O41 O42 O43 O44
14 24 34 44 I25 I26 I27 I28	O45 O46 O47 O48

Internal wiring diagram



Code structure

CS MP306M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

Quality marks:



EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19


General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	289	
PFH _D	8.38E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	8	399 part 6
Decoupled digital inputs (Jx)	4	399 part 7
Inputs for 4-20 mA analogue signals (Cx)	2	399 part 8
Inputs for frequency signals from 0 to 4 kHz (Fx)	4	400 part 9
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Pin assignment

T01 T02 T03 T04	A3 A4 A4	A5 A6 C1 C2
A1 A2 24V 0V F1A F1B F2A F2B		
PWR P1 P2	CH ACH B C1 C2	
O01 O02 O03 O04 F1A F1B F2A F2B		
OS1 OS2 OS3 OS4 I21 I22 I23 I24		
USB J25 J26 J27 J28	I41 I42 I43 I44	
O01 O02 O03 O04 I21 I22 I23 I24		
OS1 OS2 OS3 OS4 J25 J26 J27 J28	I41 I42 I43 I44	

Internal wiring diagram



Code structure

CS MP307M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	548	
PFH _D	7.27E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	24	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	8	400 part 11
Semiconductor safety output circuits (OSx)	8 PNP	400 part 13

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment

T01 T02 T03 T04	I11 I12 I13 I14	I31 I32 I33 I34
A1 A2 24V 0V	I15 I16 I17 I18	I35 I36 I37 I38
pizzato CS MP308		
PWR P1 P2	I11 I12 I13 I14	I31 I32 I33 I34
OS1 OS2 OS3 OS4	I15 I16 I17 I18	I35 I36 I37 I38
OS5 OS6 OS7 OS8	I21 I22 I23 I24	O41 O42 O43 O44
USB	I25 I26 I27 I28	O45 O46 O47 O48
OS1 OS2 OS3 OS4	I21 I22 I23 I24	O41 O42 O43 O44
OS5 OS6 OS7 OS8	I25 I26 I27 I28	O45 O46 O47 O48

Internal wiring diagram



Code structure

CS MP308M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	496	
PFH _D	7.46E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	32	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor safety output circuits (OSx)	8 PNP	400 part 13

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment

T01 T02 T03 T04	I11 I12 I13 I14	I31 I32 I33 I34
A1 A2 24V 0V	I15 I16 I17 I18	I35 I36 I37 I38
pizzato CS MP309		
PWR P1 P2	I11 I12 I13 I14	I31 I32 I33 I34
OS1 OS2 OS3 OS4	I15 I16 I17 I18	I35 I36 I37 I38
OS5 OS6 OS7 OS8	I21 I22 I23 I24	I41 I42 I43 I44
USB	I25 I26 I27 I28	I45 I46 I47 I48
OS1 OS2 OS3 OS4	I21 I22 I23 I24	I41 I42 I43 I44
OS5 OS6 OS7 OS8	I25 I26 I27 I28	I45 I46 I47 I48

Internal wiring diagram



Code structure

CS MP309M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

Quality marks:



EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19


General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	288	
PFH _D	3.46E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	8	399 part 6
Decoupled digital inputs (Jx)	8	399 part 7
Inputs for frequency signals from 0 to 4 kHz (Fx)	8	400 part 9
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Pin assignment

T01 T02 T03 T04	A3 A4 A4 A4	A5 A5 A6 A6
A1 A2 24V 0V	F1A F1B F2A F2B	F3A F3B F4A F4B
<p>pizzato CS MP310</p> <p>PWR P1 P2</p> <p>O01 O02 O03 O04 F1A F1B F2A F2B F3A F3B F4A F4B</p> <p>OS1 OS2 OS3 OS4 I21 I22 I23 I24 I41 I42 I43 I44</p> <p>USB J25 J26 J27 J28</p> <p>J45 J46 J47 J48</p>		
O01 O02 O03 O04	I21 I22 I23 I24	I41 I42 I43 I44
OS1 OS2 OS3 OS4	J25 J26 J27 J28	J45 J46 J47 J48

Internal wiring diagram



Code structure

CS MP310M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

Quality marks:



EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19


General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	363	
PFH _D	7.52E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	20	399 part 6
Inputs for 4-20 mA analogue signals (Cx)	2	399 part 8
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	4	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Pin assignment

T01 T02 T03 T04	I11 I12 I13 I14	A5 A6 C1 C2
A1 A2 24V 0V	I15 I16 I17 I18	
PWR P1 P2	I11 I12 I13 I14	CH ACH B C1 C2
O01 O02 O03 O04	I15 I16 I17 I18	
OS1 OS2 OS3 OS4	I21 I22 I23 I24	
USB I25 I26 I27 I28	I41 I42 I43 I44	
O01 O02 O03 O04	I21 I22 I23 I24	
OS1 OS2 OS3 OS4	I25 I26 I27 I28	

Internal wiring diagram



Code structure

CS MP311M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19


General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	380	
PFH _D	8,20E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x67.5x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	16	399 part 6
Decoupled digital inputs (Jx)	4	399 part 7
Inputs for frequency signals from 0 to 4 kHz (Fx)	4	400 part 9
Test outputs (Tx)	8	400 part 10
Semiconductor safety output circuits (OSx)	8 PNP	400 part 12

Pin assignment



Internal wiring diagram




Code structure

CS MP312M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19


General data

Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	434	
PFH _D	1.73E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x90x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	40	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	12	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 12

Pin assignment




Internal wiring diagram



Code structure

CS MP401M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



- ### Main features
- For safety applications up to SIL CL 3/PL e
 - Supply voltage: 24 Vdc
 - Gemnis Studio for easy and intuitive programming and program simulation
 - Large selection of logical blocks for the management of external devices and programs
 - Custom configured versions available on request

General data


Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	478	
PFH _D	7.24E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x90x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	32	399 part 6
Test outputs (Tx)	12	400 part 10
Semiconductor signalling output circuits (Ox)	8	400 part 11
Semiconductor safety output circuits (OSx)	8 PNP	400 part 13

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment



Internal wiring diagram



Code structure

CS MP402M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



Main features

- For safety applications up to SIL CL 3/PL e
- Supply voltage: 24 Vdc
- Gemnis Studio for easy and intuitive programming and program simulation
- Large selection of logical blocks for the management of external devices and programs
- Custom configured versions available on request

General data


Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	438	
PFH _D	7.42E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x90x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	40	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	8	400 part 11
Semiconductor safety output circuits (OSx)	8 PNP	400 part 13

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment



Internal wiring diagram



Code structure

CS MP403M0

Connection type	
M	Connector with screw terminals
X	Connector with spring terminals



- ### Main features
- For safety applications up to SIL CL 3/PL e
 - Supply voltage: 24 Vdc
 - Gemnis Studio for easy and intuitive programming and program simulation
 - Large selection of logical blocks for the management of external devices and programs
 - Custom configured versions available on request

General data


Parameter:	Value:	Page:
SIL CL acc. to EN IEC 62061	up to SIL CL 3	
Performance Level (PL) acc. to EN ISO 13849-1	up to PL e	
Safety category acc. to EN ISO 13849-1	up to cat. 4	
MTTF _D	473	
PFH _D	1.54E-09	
Mission time	20 years	
System response time	< 30 ms	
Dimensions (HxLxW)	111.5x90x99 mm	
Housing data		399 part 1
Environmental data		399 part 2
Supply		399 part 3
In compliance with standards		399 part 4
Programming software	Gemis Studio	399 part 5
USB port	Yes	
Safety inputs (Ix)	32	399 part 6
Test outputs (Tx)	4	400 part 10
Semiconductor signalling output circuits (Ox)	20	400 part 11
Semiconductor safety output circuits (OSx)	4 PNP	400 part 13

Quality marks:




EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Pin assignment



Internal wiring diagram



Code structure

CS MP406M0

Connection type

- M** Connector with screw terminals
- X** Connector with spring terminals

Technical data

1) Housing

Housing:	Polyamide PA 66, self-extinguishing V0 acc. to UL 94
Protection degree:	IP40 (housing) IP20 (terminal strip)
Dimensions, cable cross sections, terminal tightening torque:	Page 415, design C/E

2) Environmental

Operating temperature:	0°C ... +55°C
Storage temperature:	-20°C ... +70°C
Pollution degree:	external 3, internal 2
Overvoltage category:	II

3) Power supply

Rated voltage A1-A2 (U _n):	24 Vdc
Max. DC residual ripple in DC:	10%
Supply voltage tolerance:	±15% of U _n
Rated consumption (w/o load):	< 3 W
Protection against short circuits:	PTC resistance, I _h =1.5 A
PTC response time:	Response time > 100 ms, release time > 3 s

Internal protection against short circuits on outputs (Tx, Ox): Electronic

Maximum current output of the module as the total current of the Ox and Tx outputs:	0.5 A
Self-test duration on startup:	< 2 s

4) Compliance with standards

EN 60947-1, EN 60947-5-1, EN 60204-1, EN ISO 13849-1, EN ISO 13855, EN ISO 14118, EN ISO 12100, EN ISO 13850, EN 60529, EN 61000-6-2, EN 61000-6-3, EN 61326-1, EN 61326-3-1, EN 60664-1, EN 62061, EN IEC 63000, UL 508, CSA C22.2 No. 14, GB/T14048.5

Compliance with the requirements of:

Machinery Directive 2006/42/EC, EMC Directive 2014/30/EU, RoHS Directive 2011/65/EU.

Features approved by UL

Electrical ratings:	
Input:	4-48 inputs rated 24 V dc, 5 mA
Relay output:	230/240 Vac, 4 A general use, C300 pilot duty
Semiconductor output (when relay is not available):	up to 4 outputs rated 24 V dc, 500 mA or up to 8 outputs rated 24 Vdc, 400 mA
Semiconductor auxiliary output:	up to 32 outputs rated 24 V dc, 500 mA max
Auxiliary analogic outputs:	up to 4 rated 24 V dc, 20 mA max

Notes:

- Use 60 or 75°C copper (Cu) conductor and wire size No. 30-12 AWG, stranded or solid.
- The terminal tightening torque of 5-7 lb in.
- Only for 24 Vac/dc versions: supply from remote Class 2 source or limited voltage limited energy.

- Utiliser des conducteurs en cuivre (Cu) 60 ou 75°C rigides ou flexibles de section 30-12 AWG.
- Couple de serrage des bornes de 5-7 Lb In.
- Seulement pour les versions 24 Vac/dc, alimenter avec sources de classes 2 ou avec tension limitée et énergie limitée.

Features approved by TÜV SÜD

Rated supply voltage U _n :	24 Vdc (-15% ... +15%)
Ambient temperature:	0°C ... +55°C
Response time:	< 30 ms < 40 ms for versions with relay outputs

In compliance with standards: EN ISO 13849-1:2015 (Cat.4, PL e), EN 61508-1:2010 (SIL 3), EN 61508-2:2010 (SIL 3), EN 61508-3:2010 (SIL 3), EN 62061:2005/A1:2013/A2:2015 (SIL CL 3)

5) Gemnis Studio

The **Gemis Studio** software is the graphic development environment for the creation, simulation and debugging of programs designed for upload to Gemnis line modules.

The software is licensed to users wishing to program these modules, subject to prior registration at www.gemis.com.

From our website you can download the latest version of the software, which allows you to program the safety modules of the Gemnis family.

Gemis Studio software minimum download requirements

Computer and processor:	X86 with clock frequency of 1 GHz
Memory:	256 MB
Hard disk:	150 MB
Monitor:	Monitor with 1280×800 resolution or higher
Operating system:	Microsoft Windows 10 or higher .NET 4.6.2 Acrobat Reader

6) Input circuits (Ix)

Voltage and current in the input circuits:	24 V, 5 mA
Input signals:	0-8 V (Off), 12-24 V (On)
Galvanic separation:	No
Minimum duration of input signal:	10 ms
Input signal filtering:	Yes, maximum interference period 0.4 ms
Maximum input resistance:	100 Ω
Maximum input capacitance:	470 nF to ground 470 nF between two conductors

7) Decoupled input circuits (Jx)

Voltage and current in the input circuits:	24 V, 5 mA
Input signals:	0-8 V (Off), 12-24 V (On)
Galvanic separation:	Yes
Insulation voltage (U _i):	500 V
Minimum duration of input signal:	10 ms
Input signal filtering:	Yes, maximum interference period 0.4 ms
Maximum input resistance:	100 Ω
Maximum input capacitance:	470 nF to ground 470 nF between two conductors

NB: Voltage and current values indicated refer to the power supply terminals (Ax, see each module individually) of the board where the Jx type terminals are present.

8) Analogue input circuits (Cx)

Rated supply voltage:	24 Vdc ± 15 %
Analogue input type:	4-20 mA current loop
Measurement range:	0 ... 25 mA
Accuracy over entire measurement range:	1 % ± 1 digit
Resolution:	0.01 mA
Input resistance:	100 Ohm
Maximum applicable current:	30 mA
Managed sensors:	"source" type with 2/3 wires
Galvanic separation:	Yes
Insulation voltage (U _i):	500 V

NB: Voltage and current values indicated refer to the power supply terminals (Ax, see each module individually) of the board where the Cx type terminals are present.

**9) Frequency input circuits (Fx)**

Rated supply voltage:	24 Vdc \pm 15 %
Voltage and current in the input circuits:	24 Vdc, 7 mA
Check of the supply voltage of the connected proximity sensors:	24 Vdc \pm 20%
Maximum detectable frequency:	4 kHz
Minimum detectable frequency:	1 Hz
Frequency detection accuracy:	1 % \pm 1 digit
Resolution:	0.1 Hz
Minimum time for standstill detection:	1 s
Galvanic separation:	Yes
Insulation voltage (U_i):	500 V

NB: Voltage and current values indicated refer to the power supply terminals (Ax, see each module individually) of the board where the Fx type terminals are present.

10) Circuits with Test signals (Tx)

Signal type:	Pulsed 100 Hz 24V/0V, duty cycle 50%
Max. total current:	See Supply
Protected against short circuit:	Yes

11) Semiconductor signalling output circuits (Ox)

Output type:	PNP
Maximum current per output:	0.5 A
Max. total current:	see Supply
Impulse withstand voltage (U_{imp}):	0.8 kV
Rated insulation voltage (U_i):	32 V
Protected against short circuit:	Yes
Galvanic separation:	No

12) Semiconductor safety output circuits (OSx) with 4 safety outputs

Rated voltage 24V-0V:	24 Vdc
Number of outputs:	4
Output type:	PNP
Maximum current per output:	0.5 A
Max. total output current:	2 A
Minimum current:	10 mA
Maximum capacitive load to ground per output:	400 nF
Maximum inductive load per output:	500 mH
Protection fuse:	2 A type gG
Galvanic separation:	Yes
Impulse withstand voltage (U_{imp}):	0.8 kV
Rated insulation voltage (U_i):	32 V
Short circuit detection between outputs:	Yes
Duration of the deactivation impulses at the safety outputs:	< 300 μ s

13) Semiconductor safety output circuits (OSx) with 8 safety outputs

Rated voltage 24V-0V:	24 Vdc
Number of outputs:	8
Output type:	PNP
Maximum current per output:	0.4 A
Max. total output current:	3 A
Minimum current:	10 mA
Maximum capacitive load to ground per output:	400 nF
Maximum inductive load per output:	500 mH

Protection fuse:	4 A type gG
Galvanic separation:	Yes
Impulse withstand voltage (U_{imp}):	0.8 kV
Rated insulation voltage (U_i):	32 V
Short circuit detection between outputs:	Yes
Duration of the deactivation impulses at the safety outputs:	< 300 μ s

14) Safety relay circuits

Rated voltage 24V-0V:	24 Vdc
Contact type:	Forcibly guided contacts acc. to EN 50205
Material of the contacts:	gold-plated silver alloy
Maximum switching voltage:	230 Vac; 300 Vdc
Maximum current per contact:	6 A
Max. total current ΣI_{in}^2 :	36 A ²
Minimum current:	10 mA
Protection fuse:	4 A type gG
Maximum load:	1380 VA/W
Impulse withstand voltage (U_{imp}):	4 kV
Rated insulation voltage (U_i):	500 V
Utilization category (EN 60947-5-1):	AC15 ($U_e=230V, I_e=3A$); DC13 ($U_e=24V, I_e=4A$) (6 op. cycl./min.)
Utilization category (UL 508):	C300
Contact resistance:	< 100 m Ω
Mechanical endurance:	>10 million operating cycles
Electrical endurance:	>100,000 operating cycles
Galvanic separation:	Yes
The number and the load capacity of output contacts can be increased by using expansion modules or contactors. See pages 355-364.	

Introduction



An increasing number of users requires products which carry out several safety functions without needing the complex management of a safety PLC or the complex wiring of many traditional safety modules. Such problems arise mainly when the safety functions are typically greater than 3 or 4, and/or when managing a safety PLC software (software purchase, training courses, programming of all modules, software management and filing, updates etc.) turns out to be too great an overhead in relation to problem complexity.

Pizzato Elettrica introduces Gemnis, a series of electronic modules which are pre-programmed for specific customer applications or for generic safety macro-functions commonly used in industrial contexts. The following pages list some of the pre-programmed products for generic macro-functions commonly used in the industrial sector. These products are also available for individual purchase. Any customer requiring a product pre-programmed to their particular specification can contact the Pizzato Elettrica technical department (minimum volumes are requested).

The resulting advantages for customers typically include simplified product management (purchase of finished components) and reduced general costs (no software to be installed and managed, products are immediately operational).

All Gemnis series products are able to provide circuit solutions at SIL 3 (EN 62061), PL e (EN ISO 13849-1) or category 4 (EN ISO 13849-1) levels.


Quality marks:



EC type examination certificate: M6A 075157 0032
 UL approval: E131787
 CCC approval: 2021000305000107
 TÜV SÜD approval: Z10 075157 0031
 EAC approval: RU C-IT.YT03.B.00035/19

Code structure

CS MF201M0-P●●





Product list

Product code	Functions executed	Safety outputs	Signalling outputs	Page
CS MF201M0-P1	Monitoring of 2 guards in AND and 1 emergency stop with automatic start or manual monitored start.	3 NO	4 PNP	403
CS MF202M0-P2	Monitoring of 4 guards in AND, 1 bypass selector, 1 emergency stop, automatic start or manual monitored start, general enabling signal.	4 PNP	4 PNP	404
CS MF202M0-P3	Monitoring of 6 guards in AND (2NC contacts), 1 emergency stop, automatic start or manual monitored start.	4 PNP	4 PNP	405
CS MF202M0-P4	Monitoring of 6 guards in AND (1NO+1NC contacts), 1 emergency stop, automatic start or manual monitored start.	4 PNP	4 PNP	406
CS MF202M0-P5	Monitoring of 4 guards with independent outputs, 1 bypass selector, 1 emergency stop, automatic start or manual monitored start, general enabling signal.	4 PNP	4 PNP	407
CS MF202M0-P6	Monitoring of 2 guards, 1 bypass selector, 1 emergency stop, automatic start or manual monitored start, general enabling signal. Three instantaneous outputs and one delayed output with selector switch with 4 times. Selectable On/Off delay.	4 PNP	4 PNP	408
CS MF202M0-P7	Monitoring of 4 guards (AND linked) with switches with guard locking, operating principle "D", 1 emergency stop, monitored start. Two instantaneous outputs and two delayed outputs with selector switch with 4 times.	4 PNP	4 PNP	409
CS MF202M0-P8	Monitoring of 4 guards in AND with switches with guard locking, operating principle "E", 1 emergency stop, monitored start. Two instantaneous outputs and two delayed outputs with selector switch with 4 times.	4 PNP	4 PNP	410
CS MF204M0-P10	Monitoring of 4 guards in AND (OSSD outputs) and 1 emergency stop with automatic start or manual monitored start.	3 NO	4 PNP	411

Legend:



Movable guard monitoring



Monitoring of a movable guard with lock



Emergency stop



Start function



Bypass selector



Time selector



Enabling input



Product code
CS MF201M0-P1



Main functions

- Monitoring of 2 guards
- Monitoring of 1 emergency stop
- Automatic start or monitored manual start


Outputs

- 3 NO safety outputs
- 4 PNP signalling outputs

Technical data: see CS MP201M0
 Dimensions, cable cross sections, terminal tightening torque: page 415, design C
 Internal wiring diagram: page 418
 Terminal layout: page 418

Application program: P1

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:





CS MF202M0-P2 pre-programmed module



Product code
CS MF202M0-P2



Main functions

- Monitoring of 4 guards
- 1 bypass selector
- 1 emergency stop
- Automatic start or monitored manual start
- General enabling signal


Outputs

- 4 PNP safety outputs
- 4 PNP signalling outputs

Technical data: see CS MP202M0
 Dimensions, cable cross sections, terminal tightening torque: page 415, design C
 Internal wiring diagram: page 418
 Terminal layout: page 418


Application program: P2

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:





Product code
CS MF202M0-P3



Main functions

- Monitoring of 6 guards (2NC contacts)
- 1 emergency stop
- Automatic start or monitored manual start

Outputs

- 4 PNP safety outputs
- 4 PNP signalling outputs

Technical data: see CS MP202M0


Dimensions, cable cross sections, terminal tightening torque: page 415, design C

Internal wiring diagram: page 418

Terminal layout: page 418

Application program: P3

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:





Product code
CS MF202M0-P4

Main functions

- Monitoring of 6 guards (1NC+1NO contacts)
- 1 emergency stop
- Automatic start or monitored manual start


Outputs

- 4 PNP safety outputs
- 4 PNP signalling outputs

Technical data: see CS MP202M0
Dimensions, cable cross sections, terminal tightening torque: page 415, design C
Internal wiring diagram: page 418
Terminal layout: page 418

Application program: P4

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:





Product code
CS MF202M0-P5



Main functions

- Monitoring of 4 guards with independent outputs
- 1 bypass selector
- 1 emergency stop
- Automatic start or monitored manual start
- General enabling signal


Outputs

- 4 PNP safety outputs
- 4 PNP signalling outputs

Technical data: see CS MP202M0
Dimensions, cable cross sections, terminal tightening torque: page 415, design C
Internal wiring diagram: page 418
Terminal layout: page 418

Application program: P5

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:





CS MF202M0-P6 pre-programmed module



Product code
CS MF202M0-P6



Main functions

- Monitoring of 2 guards
- 1 bypass
- 1 emergency stop
- Automatic start or monitored manual start
- General enabling signal
- Selectable On/Off delay
- Selector switch with 4 times


Outputs

- Three instantaneous outputs and one delayed PNP safety output
- 4 PNP signalling outputs

Technical data: see CS MP202M0
 Dimensions, cable cross sections, terminal tightening torque: page 415, design C
 Internal wiring diagram: page 418
 Terminal layout: page 418

Application program: P6

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:



CS MF202M0-P7 pre-programmed module



Product code
CS MF202M0-P7



Main functions

- Monitoring of 4 guards with switches with guard locking, operating principle "D" (guard locked if solenoid is de-energised)
- 1 emergency stop
- Monitored start


Outputs

- 2 instantaneous outputs and 2 delayed PNP safety outputs with selector switch with 4 times
- 4 PNP signalling outputs
- OS4 output for door locking control

Technical data: see CS MP202M0
 Dimensions, cable cross sections, terminal tightening torque: page 415, design C
 Internal wiring diagram: page 418
 Terminal layout: page 418


Application program: P7

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:





Product code
CS MF202M0-P8



Main functions

- Monitoring of 4 guards with switches with guard locking, operating principle "E" (guard locked if solenoid is energised)
- 1 emergency stop
- Monitored start


Outputs

- 2 instantaneous outputs and 2 delayed PNP safety outputs with selector switch with 4 times
- 4 PNP signalling outputs
- OS4 output for door locking control

Technical data: see CS MP202M0
Dimensions, cable cross sections, terminal tightening torque: page 415, design C
Internal wiring diagram: page 418
Terminal layout: page 418

Application program: P8

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:



CS MF204M0-P10 pre-programmed module



Main functions

- Monitoring of 4 guards in AND (OSSD outputs)
- 1 emergency stop
- Automatic start or monitored manual start


Outputs

- 3NO safety outputs
- 4 PNP signalling outputs

Technical data: see CS MP204M0
 Dimensions, cable cross sections, terminal tightening torque: page 415, design C
 Internal wiring diagram: page 418
 Terminal layout: page 418


Application program: P10

The application program stored in the module executes one or more safety functions, as shown in the following block diagram:



Notes:The positions of the contacts shown in the diagram are shown only as examples, and they refer to expected working conditions, with machinery in operation, guards closed, and safety devices not activated. For further explanations, please see documentation relating to each specific safety function (page 399).

Legend



Definitions

Application program: The internal software component of this module which is aimed at the application.

“Power On” state: The device state, which lasts from the time it is switched on until the end of the internal controls.

“Run” state: The device state on completion of the “Power-On” phase (if no errors have been detected) in which the Application program is run.

“Error” state: The device state when a fault is detected. In this state, the module switches to the safe state, i.e., all safety outputs are open.

Fault: A fault can be internal or external to the safety module. Internal faults are autonomously detected by the module thanks to its redundant and self-monitored structure. An external fault can be detected by the application program. It follows that the definition of external fault is strictly dependent on the application (see note A).

Operation

When supplied with power, the module enters the Power-On state and runs an internal self-diagnosis. In this phase, the two processor LEDs (P1, P2) remain illuminated red for about 1 second. If the internal tests are completed without malfunction, the two LEDs are switched off, the module enters the Run state, and runs the application program. If the start tests are not passed, the module enters the Error state and the malfunction is indicated by the processor LEDs remaining illuminated red.

The green LEDs relating to the power supply and the module inputs are not controlled by processors, and they immediately begin indicating the states of the respective inputs/outputs.

When the module is in the RUN state, and no faults are detected, the two LEDs (P1, P2) remain switched off.

In the Run state, the module can detect faults external to the module, for example caused by short circuits, or invalid input states (see note A). Depending on the fault type detected, the application program may place the module in error state, to indicate the malfunction. In this case, the application program can communicate an error code by making the LEDs (P1, P2) flash in sequence.

During the Run state, simultaneously with application program execution, the module constantly runs a series of internal tests to check for correct hardware operation. If a malfunction is detected, the module state changes to Error.

Once in Error state, the module is placed in a safe condition, that is with all the safety outputs open; the application program is no longer evaluated, and neither are the system inputs. Furthermore, the semiconductor signalling outputs are left unaltered (changes in inputs do not affect them) at the value imposed by the application program before entering the error state. To reset the module, just switch it off for the required duration (see technical data) and then switch it on again.

Note A:A short circuit is not always a fault. For example, in the case of an ordinary push button for emergency stops equipped with two NC contacts, contact opening is the signal to be evaluated and a short circuit between the two contacts is a fault. In contrast, in the case of a safety mat with 4-wire technology, the opposite is true, i.e. a short circuit between the wires is the signal to be evaluated whereas wire interruption is a fault.

Fault signalling

LED PWR	LED P1 and P2	Possible fault cause
Off	Off	No power supply, incorrect connections, power wires cut, external fuses broken. Module fault.
Green	Off	Normal operation.
Green	Red	Non-restorable fault. Recommended action: Send module for repair.
Green	Red x 1 Blue x 1	Restorable fault: Overcurrent on Tx or O _x outputs. Recommended action: Disconnect the semiconductor signalling outputs (O _x) and the test outputs (Tx) to check whether an external short circuit is present.
Green	Red x 1 Blue x 2	Restorable fault. Problem detected on OS _x (short circuit towards earth or positive pole, or else short circuit between two OS _x). Suggested action: Disconnect the safety outputs to check if there are any problems on the external connections of the OS _x outputs.
Green	Red x 1 Blue x 3	Restorable fault. Module temperature outside the limits. Recommended action: Restore module temperature to within permissible limits.
Green	Red x 1 Blue x 4	Restorable fault: No power on 24V-0V terminals. Recommended action: Check the electrical connections.
Green	Blue x N	Module entered Error state at the request of the application program. Error code N. Typically due to incorrect input conditions (external short circuits, status not permitted). Recommended action: Disconnect the inputs to find any short circuits. Check the documentation supplied with the application program for further details.

**Quick description of the main safety functions (CS MF•••••)****SENSORS**

Sensor	S1C	Monitoring of one contact
Outputs	OUT	The OUT output is active when the input is closed and there is no error
	ERROR	The ERROR output is active in the case where an electrical malfunction is detected in the input signal
Parameters	None	
Examples		Start button; Stop button; Simple contact

Sensor	S1S	Monitoring of one static signal
Outputs	OUT	The OUT output is active if 24 Vdc is applied to the input
Parameters	None	
Examples		Generic sensors with PNP output; Enabling signals

Sensor	S2CD	Monitoring of two dependent contacts
Outputs	OUT	The OUT output is active when both inputs are in normal or safety state and there is no error
	ERROR	The ERROR output is active in the case where simultaneity times are not respected, or in the case where an electrical malfunction is detected at the input signals
Parameters	2NC / 1NO+1NC	Contact position in normal or safety state
	Tc	Max. time of simultaneity in seconds
Examples		Emergency stop button; rope switch; switch with two connected contacts; mode selectors with two settings, changeover; two individual switches with a time dependency

Sensor	S2CI	Monitoring of two independent contacts
Outputs	OUT	The OUT output is active when both inputs are in normal or safety state and there is no error
	ERROR	The ERROR output is active in the case where an electrical malfunction is detected in the input signals
Parameters	2NC / 1NO+1NC	Contact position in normal or safety state
Examples		Two switches; Magnetic sensor

Sensor	SSE8	Mode selector with 2 to 8 positions
Outputs	OUT	The output gives a numerical value of 1 to 8 corresponding to the active input, 0 in case of error
	ERROR	The ERROR output is active if multiple inputs are active or if no input is active, or if an electrical failure is detected in the input signals
Parameters	NumPos	Number of input signals (2 to 8)
Examples		Mode selectors with a common contact and between 2 and 8 outputs

FUNCTIONS

Function	AND	AND logical function
Outputs	OUT	The OUT output is only active if all IN input signals are present

Function	DELAY	Delayed process activation/deactivation
Outputs	OUT	The OUT output is activated if a signal is present at the IN input with a delay of Td (parameter type Don) If the signal at the IN input drops out, the OUT output is deactivated with a delay of Td (parameter type Doff)
	Parameters	Don / Doff Td

Function	NOR	NOR logical function
Outputs	OUT	The OUT output is only active in the absence of all IN input signals

Function	OR	OR logical function
Outputs	OUT	The OUT output is only active if at least one IN input signal is present

Function	PULSE	Activation of a process for a short time
Outputs	OUT	The OUT output is activated on the IN signal falling edge and remains active for the time set by Tp
Parameters	Tp	Pulse duration

Function	START	Activation of a process
Outputs	OUT	The OUT output is activated by the edge (see parameters) of the CONTROL signal if the IN input signal is present. Thus, it remains active as long as the signal is present at IN
Parameters	MAN / CNT	MAN = activation on rising edge, CNT = activation on falling edge

Function	LKTBL	Lookup table; Conversion table between data of the same type
Outputs	BOUT	Converted data at output. Initial value = 0
Parameters	Number of data	Number of data present in the table

Disclaimer:

Subject to modifications without prior notice and errors excepted. The data given in this sheet are accurately checked and refer to typical mass production values. The device descriptions and its applications, the fields of application, the external control details, as well as information on installation and operation, are provided to the best of our knowledge. This does not in any way mean that the characteristics described may entail legal liabilities extending beyond the "General Terms of Sale", as stated in the Pizzato Elettrica general catalogue. The customers/user is required to read our information and recommendations as well as the pertinent technical provisions before using the products for his own purposes.


Design A, housing width 22.5 mm

Connection data


Terminal tightening torque:	0.5 ... 0.6 Nm
Cable cross section:	0.2...2.5 mm ² 24...12 AWG

Installation


Snap-mounting on DIN rails



Connector with screw terminals



Connector with spring terminals



Screw terminals


Design B, housing width 22.5 mm

Connection data


Terminal tightening torque:	0.5 ... 0.6 Nm
Cable cross section:	0.2...2.5 mm ² 24...12 AWG

Installation

Snap-mounting on DIN rails



Connector with screw terminals



Connector with spring terminals


All values in the drawings are in mm

**Design C, housing width 45 mm****Connection data**


Terminal tightening torque: 0.5 ... 0.6 Nm
 Cable cross section: 0.2...2.5 mm²
 24...12 AWG

Installation


Snap-mounting on DIN rails



Connector with screw terminals



Screw terminals




Connector with spring terminals

Design D, housing width 22.5 mm**Connection data**


Terminal tightening torque: 0.5 ... 0.6 Nm
 Cable cross section: 0.2...2.5 mm²
 24...12 AWG

Installation


Snap-mounting on DIN rails



Connector with screw terminals



Screw terminals



Connector with spring terminals

All values in the drawings are in mm


Design E, housing width 67.5 mm

Connection data


Terminal tightening torque:	0.5 ... 0.6 Nm
Cable cross section:	0.2...2.5 mm ² 24...12 AWG

Installation

Snap-mounting on DIN rails



Screw terminals



Connector with spring terminals


Design F, housing width 90 mm

Connection data


Terminal tightening torque:	0.5 ... 0.6 Nm
Cable cross section:	0.2...2.5 mm ² 24...12 AWG

Installation

Snap-mounting on DIN rails



Screw terminals




Connector with spring terminals


All values in the drawings are in mm




Pin assignment CS MF series



CS MF201




CS MF202




CS MF204


CS MF series internal block diagram



CS MF201



CS MF202



CS MF204

M12 connectors



- M12 male connectors with cable ▶421
- M12 female connectors with cable ▶422
- M12 male connectors for panel mounting ▶423
- Field wireable M12 female connectors ▶424
- Field wireable M12 male connectors ▶424

M12 connectors, for series connections



- M12 extension cables ▶425
- M12 connectors, Y-shaped ▶426
- M12 terminating plugs for series connections ▶426

M23 connectors



- M23 male connectors for panel mounting ▶427
- M23 female connectors for panel mounting ▶428
- M23 female connectors with cable ▶429
- Field wireable M23 female connectors ▶430
- M23 extension cables with male and female connector ▶431

M8 connectors




- M8 female connectors with cable ▶432

Cable glands and adapters



- Strain relief cable glands ▶433
- Thread adapters ▶433
- Protection caps ▶434
- Threaded nuts ▶434
- Chock plugs ▶434

Tampering protection for M12 connectors



- Tampering protection for M12 connectors ▶435

LED signalling lights



- LED signalling lights ▶436

Fixing screws and plates



- Fixing plates ▶437
- Torx safety screws ▶437
- OneWay safety screws ▶437
- Bits for Torx safety screws ▶437

Junction box for series connections



- Junction box for series connection of up to 4 devices ▶438

M12 male connectors with cable




Features:

- Polyurethane connector body
- Class 6 copper conductors acc. to IEC 60228 - mobile installation
- Gold-plated contacts
- Anti-vibration self-locking ring nut
- High flexibility cable with oil resistant PVC or PUR sheath suitable to be used in drag chains, acc. to IEC 60332-1-2

Max. operating voltage:	250 Vac / 300 Vdc (4/5-pole) 30 Vac / 36 Vdc (8/12-pole)
Max. operating current:	4 A (4-5-pole); 2 A (8-pole); 1.5 A (12-pole)
Protection degree:	IP67 acc. to EN 60529, IP69K acc. to ISO 20653 (Protect the cables from direct high-pressure and high-temperature jets)
Ambient temperature:	-25°C ... +80°C, PVC sheath, fixed installation -15°C ... +80°C, PVC sheath, mobile installation -40°C ... +80°C, PUR sheath, fixed installation -25°C ... +80°C, PUR sheath, mobile installation
Wire cross-sections:	0.34 mm ² (22 AWG) for 4-pole 0.25 mm ² (23 AWG) for 5/8-pole 0.14 mm ² (26 AWG) for 12-pole
Minimum bending radius:	> cable diameter x 15
Tightening torque of the ring:	0.6 ... 0.8 Nm

Pin assignment

5 poles		8 poles	
Pin	Colour	Pin	Colour
1	Brown	1	White
2	White	2	Brown
3	Blue	3	Green
4	Black	4	Yellow
5	Grey	5	Grey
		6	Pink
		7	Blue
		8	Red



Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

article options
VF CF5PD3M-X

No. of poles

4	4 poles
5	5 poles
8	8 poles
12	12 poles

Cable sheath

P	PVC (standard)
U	PUR

Connector type

D	straight (standard)
G	angled

Connection type

M	M12x1
----------	-------

Fixing ring

	knurled ring (standard)
X	stainless steel hex ring nut

Cable length (L)

1	1 metre
2	2 metres
3	3 metres (standard)
4	4 metres
5	5 metres (standard)
...	
10	10 metres (standard)

Other lengths on request.

Stock items

VF CF5PD3M
VF CF8PD3M

Attention! For items not in stock the minimum order quantity is 100 pcs.

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com

M12 female connectors with cable






Features:

- Polyurethane connector body
- Class 6 copper conductors acc. to IEC 60228 - mobile installation
- Gold-plated contacts
- Anti-vibration self-locking ring nut made of nickel-plated brass, available on request in AISI 316L stainless steel hex version
- High flexibility cable with oil resistant PVC or PUR sheath suitable to be used in drag chains, acc. to IEC 60332-1-2

Max. operating voltage:	250 Vac / 300 Vdc (4/5-pole) 30 Vac / 36 Vdc (8/12-pole)
Max. operating current:	4 A (4-5-pole); 2 A (8-pole); 1.5 A (12-pole)
Protection degree:	IP67 acc. to EN 60529, IP69K acc. to ISO 20653 (Protect the cables from direct high-pressure and high-temperature jets)
Ambient temperature:	-25°C ... +80°C, PVC sheath, fixed installation -15°C ... +80°C, PVC sheath, mobile installation -40°C ... +80°C, PUR sheath, fixed installation -25°C ... +80°C, PUR sheath, mobile installation
Wire cross-sections:	0.34 mm ² (22 AWG) for 4-pole 0.25 mm ² (23 AWG) for 5/8-pole 0.14 mm ² (26 AWG) for 12-pole
Minimum bending radius:	> cable diameter x 15
Tightening torque of the ring:	0.6 ... 0.8 Nm

Pin assignment

4 poles		5 poles		8 poles		12 poles	
Pin	Colour	Pin	Colour	Pin	Colour	Pin	Colour
1	Brown	1	Brown	1	White	1	Brown
2	White	2	White	2	Brown	2	Blue
3	Blue	3	Blue	3	Green	3	White
4	Black	4	Black	4	Yellow	4	Green
		5	Grey	5	Grey	5	Pink
				6	Pink	6	Yellow
				7	Blue	7	Black
				8	Red	8	Grey
						9	Red
						10	Purple
						11	Grey-Pink
						12	Red-Blue



ø d: max. 6 mm

Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

article		options	
VF CA4PD3M-X			
No. of poles		Connection type	
4 4 poles		M M12x1	
5 5 poles			
8 8 poles		Fixing ring	
12 12 poles			knurled ring (standard)
		X	stainless steel hex ring nut
Cable sheath		Cable length (L)	
P PVC (standard)		1 1 metre	
U PUR		2 2 metres	
		3 3 metres (standard)	
Connector type		4 4 metres	
D straight (standard)		5 5 metres (standard)	
G angled		...	
		10 10 metres (standard)	
		Other lengths on request.	

Stock items

VF CA4PD3M
VF CA4PD5M
VF CA4PD10M
VF CA5PD3M
VF CA5PD5M
VF CA5PD10M
VF CA8PD3M
VF CA8PD5M
VF CA8PD10M
VF CA8PD20M
VF CA12PD3M
VF CA12PD5M
VF CA12PD10M
VF CA12PD20M
VF CA12PD30M
VF CA8UD5M-X
VF CA8UD10M-X
VF CA12UD10M-X

Attention! For items not in stock the minimum order quantity is 100 pcs.

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com


M12 male connectors for panel mounting



Features:

- Technopolymer or metal connector body
- Gold-plated contacts
- Wires with crimped ferrules
- Directly installable on the device, these ensure quick replacement, reducing machine down time

Max. operating voltage:	250 Vac / 300 Vdc (4/5-pole) 30 Vac / 36 Vdc (8/12-pole)
Max. operating current:	4 A (4/5-pole) 2 A (8-pole) 1.5 A (12-pole)
Protection degree:	IP67 acc. to EN 60529 IP69K acc. to ISO 20653
Ambient temperature:	-25°C ... +80°C
Tightening torque:	1 ... 1.5 Nm
Wire cross-sections:	0.5 mm ² (20 AWG) for 4/5-pole 0.25 mm ² (23 AWG) for 8-pole 0.14 mm ² (26 AWG) for 12-pole
Contact type:	gold-plated



Pin assignment

4 poles		5 poles		8 poles		12 poles	
Pin	Colour	Pin	Colour	Pin	Colour	Pin	Colour
1	Brown	1	Brown	1	White	1	Brown
2	White	2	White	2	Brown	2	Blue
3	Blue	3	Blue	3	Green	3	White
4	Black	4	Black	4	Yellow	4	Green
		5	Grey	5	Grey	5	Pink
				6	Pink	6	Yellow
				7	Blue	7	Black
				8	Red	8	Grey
						9	Red
						10	Purple
						11	Grey-Pink
						12	Red-Blue

Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

article		options	
VF CNM5MM-L100			
Body material		Wire length (L)	
M metal		8.5 cm (standard)	
P plastic		L16 16 cm	
		L100 100 cm	
		L200 200 cm	
No. of poles		Connection type	
4 4 poles		M M12x1	
5 5 poles		Connector thread (P)	
8 8 poles		M M20 x 1.5 (standard)	
12 12 poles		P PG 13.5	

Stock items

VF CNP4MM
VF CNP4PM
VF CNP5MM
VF CNP5PM
VF CNP8MM
VF CNM4MM
VF CNM4PM
VF CNM5MM
VF CNM5PM
VF CNM8MM
VF CNM8PM
VF CNM12MM-L16

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

Note: the 12-pole connector is only available in metal with M20x1.5 thread and 16 cm wires.


Field wireable M12 female connectors



Features:

- Technopolymer connector body
- Gold-plated contacts
- Screw terminals for cable screw fittings

Max. operating voltage:	250 Vac/dc (4 and 5-pole) 30 Vac/dc (8-pole)
Max. operating current:	4 A (4 and 5-pole) 2 A (8-pole)
Protection degree:	IP67 acc. to EN 60529
Ambient temperature:	-25°C ... +85°C
Wire cross-sections:	0.25 mm ² (23 AWG) ... 0.5 mm ² (20 AWG)
Tightening torque of the ring:	0.6 ... 0.8 Nm



Article	Description	no. of poles
VF CBMP4DM04	Field wireable M12 female connector, straight, for Ø 4 ... 6.5 mm multipolar cables	4
VF CBMP5DM04	Field wireable M12 female connector, straight, for Ø 4 ... 6.5 mm multipolar cables	5
VF CBMP8DM04	Field wireable M12 female connector, straight, for Ø 4 ... Ø 7 mm multipolar cables	8


Field wireable M12 male connectors



Features:

- Technopolymer connector body
- Gold-plated contacts
- Screw terminals for cable screw fittings

Max. operating voltage:	250 Vac/dc (5-pole) 30 Vac/dc (8-pole)
Max. operating current:	4 A (5-pole) 2 A (8-pole)
Protection degree:	IP67 acc. to EN 60529
Ambient temperature:	-25°C ... +85°C
Wire cross-sections:	0.25 mm ² (23 AWG) ... 0.5 mm ² (20 AWG)
Tightening torque of the ring:	0.6 ... 0.8 Nm



Article	Description	no. of poles
VF CCMP5DM04	Field wireable M12 male connector, straight, for Ø 4 ... Ø 6.5 mm multipolar cables	5
VF CCMP8DM04	Field wireable M12 male connector, straight, for Ø 4 ... Ø 7 mm multipolar cables	8

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

Series connection with Y-shaped M12 connectors

To facilitate and simplify the series wiring of the safety devices, a variety of accessories designed specifically for this purpose are available. With the help of the proven M12 round connector, safety equipment of Category 4, SIL 3 and PL e with up to 32 elements connected in series is possible. All of which is possible without the risk of connection errors and with a high IP67 protection degree.

The safety circuits consist of a 24 Vdc power supply unit, a number of extensions to the installed devices, Y connectors for branching out from the chain to each individual device and a terminating plug.

In addition to the power supply unit, a suitable safety module is used to assess the state of the safety outputs within the safety chain.

Devices suitable for series connection

The series may consist both of devices that are identical to one another (homogeneous series) or that belong to different series (mixed series).


The following Pizzato Elettrica devices may be connected in series using the Y connectors:

- ST series RFID safety sensors: ST ●●31●M●, ST ●●71●M●.
- NG series RFID safety switches with lock: NG ●●●●●●●-K950, NG ●●●●●●●-K951, NG ●●●●●●●-K952.
- NS series RFID safety switches with lock: NS ●●●●●●Q●.
- HX series safety hinge switches: HX BEE1-●●M.

Electrical connection of the chain

Pin	Colour	Connection
1	Brown	A1 Supply input +24 Vdc
2	White	OS1 Safety output
3	Blue	A2 Supply input 0 V
4	Black	OS2 Safety output
5	Grey	I4 Solenoid activation input

Note: By activating/deactivating input I4, all switches of the NG and NS series in the chain simultaneously block/open all guards. Activation and deactivation of input I4 has no effect on the ST sensors and HX hinges in the chain.



Attention! For proper operation of the devices connected in series via cables or Y connectors, it is necessary to pay particular attention to the voltage drop that occurs in the circuit. Pay particular attention to the currents and cross-sections/lengths of the used cables to ensure that the supply voltage of the components at the end of the series connection remains within the specified limit values during effective operation.

M12 extension cables



Features:

- Polyurethane connector body
- Class 6 copper conductors acc. to IEC 60228
- Gold-plated contacts
- Anti-vibration self-locking ring nut
- High flexibility cable with oil resistant PVC sheath suitable to be used in drag chains, acc. to IEC 60332-1-2

Max. operating voltage: 250 Vac / 300 Vdc (5-pole)
30 Vac / 36 Vdc (8-pole)

Max. operating current: 4 A (5-pole), 2 A (8-pole)


Protection degree: IP67 acc. to EN 60529
IP69K acc. to ISO 2653
(Protect the cables from direct high-pressure and high-temperature jets)

Ambient temperature: -25°C ... +80°C for fixed installation
-15°C ... +80°C for mobile installation

Wire cross-sections: 0.5 mm² (20 AWG) (5-pole)
0.25 mm² (23 AWG) (8-pole)

Minimum bending radius: > cable diameter x 15

Tightening torque of the ring: 0.6 ... 0.8 Nm




Code structure

VF CA5PD3M-MD

No. of poles	Connection type
5 5 poles	M M12x1
8 8 poles	
Cable sheath	Cable length (L)
P PVC	3 3 metres (standard)
	5 5 metres (standard)
Connector type	10 10 metres (standard)
D straight	Other lengths on request.

Pin assignment



Stock items

- VF CA5PD3M-MD
- VF CA5PD5M-MD
- VF CA5PD10M-MD
- VF CA8PD3M-MD
- VF CA8PD5M-MD
- VF CA8PD10M-MD

Attention! For items not in stock the minimum order quantity is 100 pcs.

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com



M12 connectors, Y-shaped, for series connections



Article	Description
VF CY201P0	M12 connector, Y-shaped, for series connections with 150 mm cable length



Article	Description
VF CY203P0	M12 connector, Y-shaped, for series connections without cable




Features:


- Polyurethane connector body
- Gold-plated contacts
- Anti-vibration self-locking ring nut
- Class 6 copper conductors acc. to IEC 60228
- High flexibility cable with oil resistant PVC sheath suitable to be used in drag chains, acc. to IEC 60332-1-2

Max. operating voltage:	30 Vac / 36 Vdc
Max. operating current:	4 A (5-pole) 2 A (8-pole)
Protection degree:	IP67 acc. to EN 60529
Ambient temperature:	-25°C ... +80°C for fixed installation -15°C ... +80°C for mobile installation
Wire cross-sections:	0.5 mm ² (20 AWG)
Minimum bending radius:	> cable diameter x 15
Tightening torque of the ring:	0.6 ... 0.8 Nm

Internal block diagram, Y-shaped connector



Pin assignment



IMPORTANT: When used in safety applications, the Y connectors must be installed in a location that is not directly accessible, so as to avoid shocks or tampering.


M12 terminating plugs for series connections




Features:

- Polyurethane connector body
- Gold-plated contacts
- Anti-vibration self-locking ring nut


Max. operating voltage:	250 Vac / 300 Vdc
Max. operating current:	4 A
Protection degree:	IP67 acc. to EN 60529
Tightening torque of the ring:	0.6 ... 0.8 Nm



Internal block diagram of the terminating plug



Pin assignment



Article	Description
VF CY100P0	M12 terminating plugs for series connections, 4-pole

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com


M23 male connectors for panel mounting



Features:


- Threaded connection M20 for installation on switches with M20 cable entry (for example: FG series and NG series)
- Nickel-plated metal connector body
- Gold-plated contacts
- 12-pole or 19-pole versions
- Wires with pre-insulated ferrules
- Directly installable on the device, these ensure quick replacement, reducing machine down time

Max. operating voltage:	250 Vac (12-pole) 100 Vac (19-pole)
Max. operating current:	3 A
Protection degree:	IP67 acc. to EN 60529 IP69K acc. to ISO 20653
Ambient temperature:	-25°C ... +80°C
Tightening torque:	1 ... 1.5 Nm
Wire cross-section:	0.34 mm ² (22 AWG)
Contact type:	gold-plated




Pin assignment

12 poles



19-pole



Pin	Colour	Pin	Colour	Pin	Colour
1	White	1	White	13	White-Green
2	Brown	2	Brown	14	Brown-Green
3	Green	3	Green	15	White-Yellow
4	Yellow	4	Yellow	16	Yellow-Brown
5	Grey	5	Grey	17	White-Grey
6	Pink	6	Pink	18	Grey-Brown
7	Blue	7	Blue	19	White-Pink
8	Red	8	Red		
9	Black	9	Black		
10	Purple	10	Purple		
11	Grey-Pink	11	Grey-Pink		
12	Red-Blue	12	Red-Blue		

Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

VF CNM12MT-L10

Body material

M metal

No. of poles

12 12 poles

19 19-pole

Wire length (L)

L10 10 cm

L16 16 cm

Note:

For applications with NG series switches, use connectors with L10 wire length.
For applications with FG series switches, use connectors with L16 wire length.

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com

M23 female connectors for panel mounting



Features:


- Threaded connection M20
- Nickel-plated metal connector body
- Gold-plated contacts
- 12-pole or 19-pole versions
- Wires with pre-insulated ferrules
- Directly installable on the device, these ensure quick replacement, reducing machine down time

Max. operating voltage:	250 Vac (12-pole) 100 Vac (19-pole)
Max. operating current:	3 A
Protection degree:	IP67 acc. to EN 60529 IP69K acc. to ISO 20653
Ambient temperature:	-25°C ... +80°C
Tightening torque:	1 ... 1.5 Nm
Wire cross-section:	0.34 mm ² (22 AWG)
Contact type:	gold-plated




Pin assignment

12 poles



19-pole



Pin	Colour	Pin	Colour	Pin	Colour
1	White	1	White	13	White-Green
2	Brown	2	Brown	14	Brown-Green
3	Green	3	Green	15	White-Yellow
4	Yellow	4	Yellow	16	Yellow-Brown
5	Grey	5	Grey	17	White-Grey
6	Pink	6	Pink	18	Grey-Brown
7	Blue	7	Blue	19	White-Pink
8	Red	8	Red		
9	Black	9	Black		
10	Purple	10	Purple		
11	Grey-Pink	11	Grey-Pink		
12	Red-Blue	12	Red-Blue		

Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

VF CPM12MT-L10

Body material	Wire length (L)
M metal	L10 10 cm
No. of poles	L20 20 cm
12 12 poles	
19 19-pole	

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com


M23 female connectors with cable




Features:

- Polyurethane connector body
- Class 5 tin-plated copper conductors acc. to IEC 60228 (12-pole)
- Class 5 tin-plated copper conductors acc. to IEC 60228 (19-pole)
- Gold-plated contacts
- Anti-vibration self-locking ring nut
- Cable with PVC sheath acc. to IEC 60332-1-2 (flame retardant)

Max. operating voltage:	160 Vac (12-pole) 63 Vac (19-pole)
Maximum operating current with 12 poles:	5 A x 0.5 mm ² (20 AWG), the currents are per conductor
Maximum operating current with 19 poles:	8 A x 0.75 mm ² + 4 A x 0.34 mm ² (22 AWG), the currents are per conductor
Protection degree:	IP67 acc. to EN 60529 IP69K acc. to ISO 20653 (Protect the cables from direct high-pressure and high-temperature jets)
Ambient temperature:	-5°C ... +70°C
Wire cross-section:	12x0,5 mm ² (12-pole) 17x0.34 mm ² + 2x0.75 mm ² (19-pole)
Minimum bending radius:	> cable diameter x 15
Tightening torque of the ring:	1 ... 1.5 Nm



Pin assignment



Pin	Colour	Pin	Colour	Pin	Colour
1	White	1	White	13	White-Green
2	Brown	2	Brown	14	Brown-Green
3	Green	3	Green	15	White-Yellow
4	Yellow	4	Yellow	16	Yellow-Brown
5	Grey	5	Grey	17	White-Grey
6	Pink	6	Pink	18	Grey-Brown
7	Blue	7	Blue	19	White-Pink
8	Red	8	Red		
9	Black	9	Black		
10	Purple	10	Purple		
11	Grey-Pink	11	Grey-Pink		
12	Red-Blue	12	Red-Blue		

Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

VF CA12PD20S

No. of poles	Connection type
12 12 poles	S M23x1
19 19-pole	
Cable sheath	Cable length (L)
P PVC	5 5 metres
	10 10 metres
Connector type	20 20 metres
D straight	30 30 metres

Other lengths on request.

Stock items

VF CA12PD10S
VF CA12PD20S
VF CA12PD30S
VF CA19PD5S
VF CA19PD10S
VF CA19PD20S
VF CA19PD30S

Attention! For items not in stock the minimum order quantity is 50 pcs.

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com


Field wireable M23 female connectors



Features:

- Nickel-plated metal connector body
- Gold-plated contacts
- 12-pole or 19-pole versions

Max. operating voltage:	250 Vac (12-pole) 100 Vac (19-pole)
Max. operating current:	8 A
Protection degree:	IP67 acc. to EN 60529 IP69K acc. to ISO 20653
Ambient temperature:	-40°C ... +125°C
Tightening torque of the ring:	1 ... 1.5 Nm
Pollution degree:	3




Pin configuration

12 poles




clockwise numbering



counterclockwise numbering

19-pole



clockwise numbering



Article	Description
VF AC2205	Mounting key

Note: Article required for opening and wiring of connector.

Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

VF CBSM12TC07

Connection type

S M23x1

Body material

M metal

No. of poles

12 12 poles

19 19-pole

Connector type

T clockwise numbering (standard)

D counterclockwise numbering

Cable diameter

07 Ø 7 ... 12 mm

Pin connection type

C crimp connection (standard) 0.34 ... 1 mm²

S solder connection 0.34 ... 1 mm²

Note: Use appropriate crimp pliers for crimp connections (e.g., Knipex, article number 97 52 63).

Stock items

VF CBSM12TC07

VF CBSM19TC07

VF CBSM12TS07

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com


M23 extension cables with male and female connector



Features:

- Polyurethane connector body
- Class 5 tin-plated copper conductors acc. to IEC 60228
- Gold-plated contacts
- Anti-vibration self-locking ring nut
- Cable with PVC sheath acc. to IEC 60332-1-2 (flame retardant)

Max. operating voltage:	63 Vac
Maximum operating current with 19 poles:	8 A x 0.75 mm ² + 4 A x 0.34 mm ² (22 AWG), the currents are per conductor
Protection degree:	IP67 acc. to EN 60529 IP69K acc. to ISO 20653 (Protect the cables from direct high-pressure and high-temperature jets)
Ambient temperature:	-5°C ... +70°C
Wire cross-section:	17x0.34 mm ² + 2x0.75 mm ²
Minimum bending radius:	> cable diameter x 15
Tightening torque of the ring:	1 ... 1.5 Nm




Pin assignment

19-pole male



19-pole female



Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

VF CA19PD5S-SD

No. of poles	19	19-pole	Connection type	S	M23x1
Cable sheath	P	PVC	Cable length (L)	5	5 metres
Connector type	D	straight	10	10 metres	
			20	20 metres	
			Other lengths on request.		

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com


M8 female connectors with cable



Features:

- Polyurethane connector body
- Class 6 copper conductors acc. to IEC 60228
- Gold-plated contacts
- Anti-vibration self-locking ring nut
- High flexibility cable with oil resistant PVC or PUR sheath suitable to be used in drag chains, acc. to IEC 60332-1-2

Max. operating voltage:	60 Vac / 75 Vdc
Max. operating current:	4 A
Protection degree:	IP67 acc. to EN 60529 IP69K acc. to ISO 20653 (Protect the cables from direct high-pressure and high-temperature jets)
Ambient temperature:	-25°C ... +80°C for fixed installation -15°C ... +80°C for mobile installation
Wire cross-sections:	0.25 mm ² (23 AWG)
Minimum bending radius:	> cable diameter x 15
Tightening torque of the ring:	0.3 ... 0.5 Nm



Pin assignment

4 poles



Pin	Colour
1	Brown
2	White
3	Blue
4	Black

Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office.

VF CA4PD3K

No. of poles	4 4 poles	Connection type	K M8x1
Cable sheath	P PVC (standard) U PUR	Cable length (L)	1 1 metre 2 2 metres 3 3 metres (standard) 4 4 metres 5 5 metres (standard) ... 10 10 metres
Connector type	D straight	Other lengths on request.	

Stock items

VF CA4PD3K
VF CA4PD5K

Attention!

For items not in stock the minimum order quantity is 100 pcs.

ATTENTION: always disconnect the power supply before removing the connector. The connector is not suitable for separation of electrical loads.

All values in the drawings are in mm

→ The 2D and 3D files are available at www.pizzato.com

Strain relief cable glands

Packs of **10 pcs.**

This particular design ensures high resistance to traction of the cable glands. All cable glands are also suitable for a wide range of cable diameters.

Suitable for circular cross-section cables only.


Features:

Body and ring material: technopolymer without halogen

Protection degree: IP67 acc. to EN 60529

Tightening torque: 3 ... 4 Nm (PG 13.5/M20)

2 ... 2.5 Nm (PG 11/M16)



	Article	Description	A	⬡M	N	O	P
Metric threads	VF PAM25C7N	M25x1.5 cable gland for one cable Ø 10 ... 17 mm	⊙	33	10	31	M25x1.5
	VF PAM20C6N	M20x1.5 cable gland for one cable Ø 6 ... 12 mm	⊙	24	9	24	M20x1.5
	VF PAM20C5N	M20x1.5 cable gland for one cable from Ø 5 ... 10 mm	⊙	24	9	24	M20x1.5
	VF PAM20C3N	M20x1.5 cable gland for one cable Ø 3 ... 7 mm	⊙	24	9	24	M20x1.5
	VF PAM16C5N	M16x1.5 cable gland for one cable Ø 5 ... 10 mm	⊙	22	7.5	23	M16x1.5
	VF PAM16C4N	M16x1.5 cable gland for one cable Ø 4 ... 8 mm	⊙	22	7.5	23	M16x1.5
	VF PAM16C3N	M16x1.5 cable gland for one cable Ø 3 ... 7 mm	⊙	22	7.5	23	M16x1.5
	VF PAM20CBN	M20x1.5 multi-hole cable gland for 2 cables Ø 3 ... 5 mm	⊙	24	9	23	M20x1.5
	VF PAM20CDN	M20x1.5 multi-hole cable gland for 3 cables Ø 1 ... 4 mm	⊙	24	9	23	M20x1.5
	VF PAM20CEN	M20x1.5 multi-hole cable gland for 3 cables Ø 3 ... 5 mm	⊙	24	9	23	M20x1.5
	VF PAM20CFN	M20x1.5 multi-hole cable gland for 4 cables Ø 1 ... 4 mm	⊙	22	9	23	M20x1.5
PG threads	VF PAP13C6N	PG 13.5 cable gland for one cable from Ø 6 ... 12 mm	⊙	24	9	24	PG 13.5
	VF PAP13C5N	PG 13.5 cable gland for one cable from Ø 5 ... 10 mm	⊙	24	9	24	PG 13.5
	VF PAP13C3N	PG 13.5 cable gland for one cable from Ø 3 ... 7 mm	⊙	24	9	24	PG 13.5
	VF PAP11C5N	PG 11 cable gland for one cable from Ø 5 ... 10 mm	⊙	22	7.5	23	PG 11
	VF PAP11C4N	PG 11 cable gland for one cable from Ø 4 ... 8 mm	⊙	22	7.5	23	PG 11
	VF PAP11C3N	PG 11 cable gland for one cable from Ø 3 ... 7 mm	⊙	22	7.5	23	PG 11

Thread adapters


Packs of **100 pcs.**

Thread adapters make it possible to fulfil requests for switches with a different thread to those generally found in stock. This means it is possible to offer customers a single product type with various threaded connections, while only having to stock the product itself and many kinds of adapters.

Features:

Body material: glass fibre reinforced technopolymer

Tightening torque: 3 ... 4 Nm




Article	Description	X	Y	Z	K	⬡E
VF ADPG13-PG11	Adapter from PG 13.5 to PG 11	PG 13.5	PG 11	9	12	22
VF ADPG13-M20	Adapter from PG 13.5 to M20x1.5	PG 13.5	M20x1.5	9	14	24
VF ADPG13-1/2NPT	Adapter from PG 13.5 to 1/2 NPT	PG 13.5	1/2 NPT	9	14	24
VF ADPG11-1/2NPT	Adapter from PG 11 to 1/2 NPT	PG 11	1/2 NPT	7	14	24
VF ADPG11-PG13	Adapter from PG 11 to PG 13.5	PG 11	PG 13.5	7	14	24
VF ADM20-1/2NPT	Adapter from M20x1.5 to 1/2 NPT	M20x1.5	1/2 NPT	9	14	24

Protection caps

Packs of **10 pcs.****Features:**

Body material: technopolymer, self-extinguishing
 Protection degree: IP67 acc. to EN 60529
 IP69K acc. to ISO 20653
 Tightening torque: 1.2 ... 1.6 Nm
 Cross-recessed screw: PH3




Article	Description	A	B
VF PTM20	Protection cap M20x1.5	24	M20x1.5
VF PTG13.5	Protection cap PG13.5	24	PG 13.5

Threaded nuts

Packs of **10 pcs.****Features:**

Tightening torque: 1.2 ... 2 Nm




	Article	Description	S	CH	P
Plastic	VF DFPM25	M25x1.5 threaded technopolymer nut	6	32	M25x1.5
	VF DFPM20	M20x1.5 threaded technopolymer nut	6	27	M20x1.5
	VF DFPM16	M16x1.5 threaded technopolymer nut	5	22	M16x1.5
	VF DFPP13	PG13.5 threaded technopolymer nut	6	27	PG 13.5
Metal	VF DFMM20	M20x1.5 threaded nut in nickel-plated brass	3	23	M20x1.5

Chock plugs

Packs of **100 pcs.****Features:**

Body material: technopolymer
 Protection degree: IP54 acc. to EN 60529
 Tightening torque: 0.8 ... 1 Nm



Note: Use a socket wrench for tightening.

Article	Description	A	B
VF PFM20C8N	Chock plug for one cable Ø 8 ... 12 mm, threaded, M20x1.5	7.5	M20x1.5
VF PFM20C4N	Chock plug for one cable Ø 4 ... 8 mm, threaded, M20x1.5	3.5	M20x1.5

Tampering protection for M12 connectors

Packs of 10 pcs.



Features:




These tampering protections are composed of two identical snap-on shells. They are applied to the device connectors, thereby making them inaccessible. The shells can only be removed by breaking them. Thus, any attempt to tamper with them will be immediately evident.

The protection can be installed quickly and easily by pressing the two shells lightly into place.

The protections are suitable for all devices with an M12 connector (e.g. NS, ST, SR series) but they can also be used for junctions between cables with male - female connectors.

A version made of detectable plastic is available for the food industry, and it can easily be detected during the process using common optical vision technologies, X-rays or metal detectors.

Installation:




Article	Description	Colour / material
VF PC1A9	Tamper-proof protection for device-side connector	● Grey technopolymer
VF PC2A9	Tamper-proof protection for male - female connector	● Grey technopolymer
VF PC1B6	Tamper-proof protection for device-side connector	● Blue detectable technopolymer
VF PC2B6	Tamper-proof protection for male - female connector	● Blue detectable technopolymer

Door holding magnets



Article	Description
SM H9ZF	Door holding magnet (holding force 40 N)
SM H9ZQ	Door holding magnet (holding force 40 N, opposite polarity to SM H9ZF)

Holding magnets for use on machinery doors. The magnets are sealed inside a plastic cover and will not rust even in damp environments.



LED signalling lights

Packs of 5 pcs.



These signalling lights with high luminosity LEDs are used for signalling that an electric contact has changed its state inside the switch. They can be installed on switches of the FL, FX, FZ, FW, FG, FY, NG or FS series by screwing them on one of the conduit entries not used for electric cables. They can be used for many different purposes: for example, to signal, from a distance, whether the switch has been actuated; whether the guard has closed correctly; or whether the guard is locked or unlocked. The inner part can rotate in such a way that it can be wired and screwed on the switch without any risk of twisting the wires.

Features:

Protection degree:

IP67 acc. to EN 60529

Ambient temperature:

IP69K acc. to ISO 20653

Operating voltage U_n :

-25°C ... +70°C

24 Vac/dc (10 mA)

120 Vac (20 mA)

230 Vac (20 mA)

Tolerance on the supply voltages:

 $\pm 15\%$ of U_n

Operating current:

10 mA

Connection system:

PUSH-IN spring type

Cross-section of rigid/flexible wires w. wire-end sleeve:

min. 1 x 0.34 mm² (1 x AWG 24)max. 1 x 1.5 mm² (1 x AWG 16)

Wire cross-section with pre-insulated wire-end sleeve:

min. 1 x 0.34 mm² (1 x AWG 24)max. 1 x 0.75 mm² (1 x AWG 18)



Tightening torque:

1.2 ... 2 Nm


Wire stripping length (x):

min.: 8 mm

max.: 12 mm



Application examples



Status indicator for safety rope switches



Indication of unlocked door

Code structure

Attention! The feasibility of a code number does not mean the effective availability of a product. Please contact our sales office

VF SL1A3PA1

Operating voltage

1	24 Vac/dc
3	120 Vac
4	230 Vac

Type of light source

A	Standard LED with continuous light
----------	------------------------------------

Body design

A	Total height 40 mm, spherical lens, threading M20x1.5 mm
----------	--

Connection type

P	PUSH-IN terminal strip
----------	------------------------

Lens colour

2	White
3	Red
4	Green
5	Yellow

Stock items

VF SL1A3PA1
VF SL1A5PA1

Fixing plates



Metal fixing plate, for fixing rope switches on the ceiling.
The plate is provided with bore holes for fastening switches of the FD, FL, FC, FP, FR, FM, FZ, FX, FK series. It is supplied without screws.

Article	Description
VF SFP2	Ceiling fixing plate

Fixing plates



Fixing plate (complete with fastening screws) provided with long slots for adjusting the operating point.
Each plate is provided with two pairs of mounting holes, one for standard switches and one for switches with reset device. The actuator thus always has the same actuating point.

Article	Description
VF SFP1	Fixing plate (FR series)
VF SFP3	Fixing plate (FX series)

Torx safety screws

Packs of **10 pcs.**



Pan head screws with Torx fitting and pin, stainless steel.
Use a thread locker where required for applications acc. to EN ISO 14119.

Article	Description
VF VAM4X10BX-X	M4x10 screw, with Torx T20 fitting, AISI 304
VF VAM4X15BX-X	M4x15 screw, with Torx T20 fitting, AISI 304
VF VAM4X20BX-X	M4x20 screw, with Torx T20 fitting, AISI 304
VF VAM4X25BX-X	M4x25 screw, with Torx T20 fitting, AISI 304
VF VAM4X30BX-X	M4x30 screw, with Torx T20 fitting, AISI 304
VF VAM5X10BX-X	M5x10 screw, with Torx T25 fitting, AISI 304
VF VAM5X15BX-X	M5x15 screw, with Torx T25 fitting, AISI 304
VF VAM5X20BX-X	M5x20 screw, with Torx T25 fitting, AISI 304
VF VAM5X25BX-X	M5x25 screw, with Torx T25 fitting, AISI 304
VF VAM5X35BX-X	M5x35 screw, with Torx T25 fitting, AISI 304
VF VAM5X45BX-X	M5x45 screw, with Torx T25 fitting, AISI 304

OneWay safety screws


Packs of **10 pcs.**



Pan head screws with OneWay fitting in stainless steel.
This screw type cannot be removed or tampered with using common tools. Ideal for fixing safety device actuators in accordance with EN ISO 14119.

Article	Description
VF VAM4X10BW-X	M4x10 screw, with OneWay fitting, AISI 304
VF VAM4X15BW-X	M4x15 screw, with OneWay fitting, AISI 304
VF VAM4X20BW-X	M4x20 screw, with OneWay fitting, AISI 304
VF VAM4X25BW-X	M4x25 screw, with OneWay fitting, AISI 304
VF VAM5X10BW-X	M5x10 screw, with OneWay fitting, AISI 304
VF VAM5X15BW-X	M5x15 screw, with OneWay fitting, AISI 304
VF VAM5X20BW-X	M5x20 screw, with OneWay fitting, AISI 304
VF VAM5X25BW-X	M5x25 screw, with OneWay fitting, AISI 304

Bits for Torx safety screws



Bits for Torx safety screws with pin, with 1/4" hexagonal connection.

Article	Description
VF VAIT1T20	Bits for M4 screws with Torx T20 fitting
VF VAIT1T25	Bits for M5 screws with Torx T25 fitting
VF VAIT1T30	Bits for M6 screws with Torx T30 fitting

Junction box for series connection of up to 4 devices




This accessory allows easy and precise series connection of up to 4 devices. Thanks to the numbered terminals and to the internal circuit, it is sufficient to connect the conductors in the slots provided with the practical and fast PUSH-IN spring connections. Thanks to the four internal microswitches, it is possible to easily and immediately direct the device signalling outputs (open or closed, locked or unlocked) to one of the four available auxiliary channels and then manage the information independently for each channel through a PLC.

Features:

- Material:** Self-extinguishing shock-proof polycarbonate with double insulation, UV-resistant and glass fibre reinforced
- Material of the screws:** Stainless steel
- Protection degree:** IP67 acc. to EN 60529, IP69K acc. to ISO 20653, with cable gland of equal or higher protection degree
- Conduit entries:** 2x M20 - 1/2 NPT knock-out side entries
2x M20 - 1/2 NPT - M25 knock-out side entries
2x M16 knock-out base entries
- Ambient temperature:** -40°C ... +80°C
- Tightening torque of the cover screws:** 1 ... 1.4 Nm
- Connection system:** PUSH-IN spring type
- Cross-section of rigid/flexible wires w. wire-end sleeve:** min. 1 x 0.34 mm² (1 x AWG 24)
max. 1 x 1.5 mm² (1 x AWG 16)
- Wire cross-section with pre-insulated wire-end sleeve:** min. 1 x 0.34 mm² (1 x AWG 24)
max. 1 x 0.75 mm² (1 x AWG 18)
- Wire stripping length (x):** min.: 8 mm
max.: 12 mm




Pin assignment




Article	Description
VF CY302P0	Junction box for series connection of up to 4 devices

Terminal box	Connection	Terminal box	Connection
1A / 1B	A1 Supply input +24 Vdc	1C	A1 Supply input +24 Vdc
2A / 2B	A2 Supply input 0 V	2C	OS1 Safety output
3A / 3B	OS1 / IS1 Safety output / safety input	3C	A2 Supply input 0 V
4A / 4B	OS2 / IS2 Safety output / safety input	4C	IS1 Safety input
5A / 5B	Auxiliary connection	5C	O3 Signalling output, actuator inserted
6A / 6B	Auxiliary connection	6C	OS2 Safety output
7A / 7B	OAU1 Auxiliary output Oaux1	7C	IS2 Safety input
8A / 8B	OAU2 Auxiliary output Oaux2	8C	I4 Solenoid activation input
9A / 9B	OAU3 Auxiliary output Oaux3		
10A / 10B	OAU4 Auxiliary output Oaux4		
11A / 11B	I4 Solenoid activation input		

Example of series connection of 4 NG series switches



Wiring diagram



Installation of single switches with safety functions

- Use **only** switches with the symbol  (see figure on the side).
- Connect the safety circuit to **the NC normally closed contacts (11-12, 21-22 or 31-32)**.
- **The NO normally open contacts (13-14, 23-24, 33-34)** should be used **only for signalling**; these contacts are not to be connected with the safety circuit. However, if two or more switches are used on the same guard, a connection can be established between the NO contacts and the safety circuit. In this case at least one of the two switches must have positive opening and a normally closed contact NC (11-12, 21-22 or 31-32) must be connected to the safety circuit.
- Actuate the switch **at least up to the positive opening travel** shown in the travel diagrams with symbol .
- The actuation system must be able to exert a force that is greater than the **positive opening force**, as specified in brackets below each article, next to the minimum force value.
- The device must be affixed in compliance with EN ISO 14119.



Whenever the machine guard is opened and during the whole opening travel, **the switch must be pressed directly** (fig. 1) **or through a rigid connection** (fig. 2).

Only in this way the positive opening of the normally closed NC contacts (11-12, 21-22, 31-32) is guaranteed.






Fig.1



FD 615-M2



FD 615-M2

Fig.2

In safety applications with only one switch for each guard, the switches **must never be activated by a release** (fig. 3 and 4) **or through a non rigid connection** (i.e. by a spring).




Fig.3





Fig.4

Mechanical stop


Acc. to EN ISO 14119 paragraph 5.2 letter h) the position sensors must not be used as mechanical stop.



The actuator must not exceed the max. travel as indicated in the travel diagrams.

The guard must not use the switch head as a mechanical stop.

The actuator must not strike directly against the switch head.



The actuator must not strike directly against the magnetic sensor.

The opening angle of safety hinge switch HP, HC and HX series must not exceed 180°.

Actuation modes

Recommended application	Application to avoid This application is possible, but increased mechanical stress may shorten the operating life of the switch	Forbidden application